

Contents

1. Introduction	11
1.1 Motivation	12
1.2 Review of the dynamic load identification methods	13
1.3 Real-time systems	18
1.4 Advantages of the proposed piezo-techniques	20
1.5 Thesis objectives	23
1.6 Composition of the thesis	25
2. Road Weigh-in-Motion	27
2.1 Introduction	27
2.2 Review of WIM systems	27
2.2.1 Types of sensors used in WIM systems	29
2.2.2 Calibration of WIM sensors	32
2.2.3 Factors influencing the measurements by the WIM sensors	33
2.3 New concept of traffic load identification	37
2.3.1 General idea of the beam-shape device	37
2.3.2 Laboratory tests of the beam-shape device	38
2.3.3 Numerical analysis of the beam-shape device	38
2.3.4 Modified load identification algorithm	47
2.3.5 Road installation of the beam-shape device	50
2.4 Development of the new plate-shape device	56
2.4.1 General idea of the plate-shape device	57
2.4.2 Numerical analysis of the plate-shape device	57
2.4.3 Road installation of the plate-shape device	61
2.5 Final remarks	67
3. Weigh-in-Motion system for the railway transport	69
3.1 Introduction	69
3.2 A review of the existing railways WIM systems	69
3.3 The proposed WIM system	71
3.3.1 General idea of the WIM system for railways	72
3.3.2 Proposed methods of dynamic load identification	74
3.4 Pioneer installation of the proposed WIM system <i>in situ</i>	76

3.4.1 Experimental tests of the piezo-based WIM system	77
3.4.2 Performance comparison of piezo-sensors and strain gauges	80
3.5 Numerical model vs. experiments	84
3.5.1 A review of railway track models	84
3.5.2 Description of the proposed model	85
3.6 Final remarks	92
4. Impact load identification	93
4.1 Introduction	93
4.2 Impact load parameters characteristics	95
4.3 Experimental test stand	97
4.4 Numerical model of the system	98
4.5 Impact scenarios	102
4.5.1 Experimental tests of impact scenarios	102
4.5.2 Numerical simulation of impact scenarios	108
4.6 Impact identification based on “Peak-to-peak” approach	112
4.6.1 The idea	112
4.6.2 Determination of time instants when colliding objects relative velocity vanishes	116
4.6.3 Verification of the method	119
4.7 Response map approach	123
4.7.1 The idea	123
4.7.2 Selection of parameters for the response maps	125
4.7.3 Verification of response map approach	128
4.8 “Impactometer” device concept	129
4.9 Final remarks	131
5. Concluding remarks	133
5.1 Thesis summary	133
5.2 Key achievements	135
A. Finite element modelling of piezoelectric sensors	137
B. Small testing stand of the beam-shape device	141
C. Simplified load identification algorithm	143
D. Full size testing stand of the beam-shape device	147
E. Modal analysis of FE models	153
F. Real-time impact mass identification methods	157
F.1 Mass identification based on force and acceleration	157
F.2 Mass identification based on impulse and momentum change	160

G. The restitution coefficient discussion	163
H. Sensitivity analysis of “Peak-to-peak” approach	165
Podsumowanie	168
Bibliography	171

I would like to gratefully acknowledge the financial support obtained via the following projects and funds:

- Project “Health Monitoring and Lifetime Assessment of Oil-Field Equipment”, No. POIG.01.01.02-00-008-01 from the EU Structural Funds in Poland, co-financed by the Ministry of Science and Higher Education;
- Structural Funds in the Operational Program “Innovative Economy” (S.I.O.), Project “Innovative material technologies in new energy sources”, No. 1.1.2.1.01.01.01.01.00-00, co-financed by the European Regional Development Fund;
- Project “Innovative techniques for small wind turbines”, No. 1.1.2.1.01.01.01.01.00-00, co-financed by the European Regional Development Fund.

I would like to express my gratitude to the Polish Ministry of Science and Higher Education for financial support carried out via the research project No. N503 373 33/2007.

I would like to express my thanks to Dr. Janusz Gajewski, Dr. Stefan Kowalewski, Dr. Krzysztof Kula, Dr. Paweł Kukielka for their assistance in preparing the present article, especially prof. Janusz Gajewski for many valuable advice and his guidance. I would like to thank my colleagues in the laboratory, Dr. Tomasz Stępniewski, Mr. Leszek Skubiszak and Mr. Michał Ruk for their help and nice cooperation during the preparation of many experiments. In the eighties of the last century part of the work reported in this article was carried out there, my partner, closely connected to me during those years, dr. hab. inż. Maria