

IPPT Reports on Fundamental Technological Research
2/2025

Semi-Active Control of Energy Transfer Between Vibration Modes in Mechanical Structures

Mariusz Ostrowski

Institute of Fundamental Technological Research
Polish Academy of Sciences
Warsaw 2025

Contents

1. Introduction	27
1.1. Literature review	27
1.1.1. Passive versus active vibration control	28
1.1.2. Semi-active control	34
1.1.3. Semi-active control for light-weight structures	38
1.1.4. Modal control	43
1.1.5. Energy harvesting	48
1.2. Motivation, aims, assumptions and scope of the thesis	51
1.3. Contributions	56
2. Dynamics of the reconfigurable structure equipped with lock- able joints	59
2.1. Dynamics of a reconfigurable system with two degrees of freedom	60
2.1.1. Reconfigurable system with 2 DOFs	60
2.1.2. Phase 1: unlocked joint	61
2.1.3. Phase 2: locking effect	62
2.1.4. Phase 3: unlocking of the joint	65
2.1.5. Selection of the modal basis	66
2.1.6. Relaxed kinematic constraints with (equivalent) viscous model of the joint	68
2.2. Dynamics of reconfigurable MDOF structures	77
2.2.1. Lockable joints in MDOF structure	77
2.2.2. Structure dynamics	80
2.2.3. Unlocked and locked modal basis, modal coupling effect .	82
2.2.4. Energy transfer between vibration modes	87
3. Semi-active control strategy	93
3.1. Quantities required to be measured and hierarchical feedback ar- chitecture	93
3.1.1. Issues to be addressed and selected measured quantities .	93
3.1.2. Realisation of measurement and its representation in the model	94

3.2. Optimal sensor placement	97
3.2.1. Error of the modal filter and its metrics	97
3.2.2. Effective Independence concept	99
3.2.3. Convex relaxation approach for sensor layout optimisation	100
3.3. Optimal placement of the lockable joints	102
3.3.1. Controllability in the control of modal energy transfer – issues	102
3.3.2. Proposed controllability metric	102
3.3.3. Implementation for various applications	104
3.4. Semi-active control – potential applications	104
3.4.1. Implementation for vibration suppression	105
3.4.2. Implementation for energy harvesting	110
3.4.3. Illustrative example of control of the system with two degrees of freedom	111
4. Numerical study	119
4.1. Vibration attenuation	119
4.1.1. Prestress accumulation–release (PAR) as a benchmark	119
4.1.2. Eight-bay smart structure equipped with two optimally placed lockable joints	120
4.1.3. Eight-bay smart structure with two non-optimally placed lockable joints	132
4.2. Energy harvesting	140
4.2.1. Smart structure enhancing energy harvesting process	141
4.2.2. Model of electromagnetic energy harvester	143
4.2.3. Interaction between the energy harvester and the structure	145
4.2.4. Optimal EMEH placement and tuning for preselected targeted unlocked vibration mode	148
4.2.5. Modal energy transfer for enhancement of the energy harvesting process	148
5. Experimental verification	163
5.1. Experimental setup	163
5.1.1. Smart structure equipped with 6 semi-active joints	163
5.1.2. Experimental modal analysis	165
5.2. Numerical model of the real structure	167
5.2.1. Initial finite element model	167
5.2.2. Model updating	169
5.2.3. Material damping	176
5.3. Hardware control loop	176
5.3.1. Equipment and its limitations	176
5.3.2. Modal filtering and unlocked vibration modes	177

5.3.3. Preparation of the control algorithm	178
5.4. Vibration attenuation	180
5.4.1. Modal controllability by various pairs of lockable joints	180
5.4.2. Mitigation of free structural vibration	184
5.4.3. Mitigation of the forced structural vibration	190
5.5. Energy transfer to the targeted mode	200
6. Conclusions	207
Appendix A. Three dimensional mode shapes of the laboratory- scale frame	211
Bibliography	219